

### Overview

### HPE OfficeConnect 1920S Switch Series



### Models

|                                                    |        |
|----------------------------------------------------|--------|
| HPE OfficeConnect 1920S 8G Switch                  | JL380A |
| HPE OfficeConnect 1920S 24G 2SFP Switch            | JL381A |
| HPE OfficeConnect 1920S 48G 4SFP Switch            | JL382A |
| HPE OfficeConnect 1920S 8G PPOE+ 65W Switch        | JL383A |
| HPE OfficeConnect 1920S 24G 2SFP PPOE+ 185W Switch | JL384A |
| HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W Switch  | JL385A |
| HPE OfficeConnect 1920S 48G 4SFP PPOE+ 370W Switch | JL386A |

### Key features

- Customized operation using intuitive Web interface
- Layer 3 static routing with 32 routes for network segmentation and expansion
- Access control lists for granular security control
- Spanning Tree Protocol: STP, RSTP, and MSTP
- 8-, 24- and 48-port non-PoE+ models are fanless for quiet operation

## Overview

- HPE Limited Lifetime warranty

---

## Product overview

The HPE OfficeConnect 1920S Switch Series consists of advanced smart-managed fixed-configuration Gigabit switches designed for small businesses in an easy-to-administer solution.

The series consists of seven switches including 8-, 24- and 48-port Gigabit Ethernet switches and 8-, 24- and 48-port PoE+ models of which half the ports are POE+ capable. An additional 24-port PoE+ model is available that provides PoE+ on all 24-ports. All ports provide non-blocking Gigabit per performance. Some models include SFP ports for fiber connectivity and the 8-, 24- and 48-port non PoE+ models are fanless, making them ideal for office deployments. All HPE OfficeConnect 1920S Switches support flexible installation options, including mounting on wall, under table, or on desktop. The 8-port Gigabit Ethernet model can be powered by an upstream Power over Ethernet switch for environments where no inline power is available.

The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products. These switches provide a great value, and includes features to satisfy even the most advanced small business networks. Customizable features include basic Layer 2 features like VLANs and link aggregation, as well as advanced features such as Layer 3 static routing, IPv4 and IPv6 Host mode, ACLs, and Spanning Tree Protocols. HPE OfficeConnect 1920S Switch Series includes a Limited Lifetime Warranty. This warranty provides advance hardware replacement with next business day shipment in most countries, limited 24x7 telephone support available from HPE for the first 90 days, and limited electronic and business hours telephone support is available from HPE for the entire warranty period.

---

## Features and benefits

### Management

- **Simple Web management**  
Allows for easy management of the switch—even by nontechnical users—through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS)
- **SNMPv1, v2c, and v3**  
Facilitate management of the switch, as the device can be discovered and monitored from an SNMP management station
- **Complete session logging**  
Provides detailed information for problem identification and resolution
- **Port mirroring**  
Enables traffic on a port or VLAN to be simultaneously sent to a network analyzer for monitoring
- **Dual flash images**  
Provide independent primary and secondary operating system files for backup while upgrading
- **Network Time Protocol (NTP)**  
Synchronizes timekeeping among distributed time servers; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Manual network time configuration**  
Manually set the date and time on the switch in the absence of an NTP server
- **Default DHCP client mode**  
Allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of a DHCP server on the network, the switch falls back to the static address 192.168.1.1
- **FTP and TFTP**  
Provides different mechanisms for configuration updates; FTP allows bidirectional transfers over a TCP/IP network; trivial FTP (TFTP) is a simpler method using user Datagram Protocol (UDP)
- **Remote monitoring (RMON)**  
Remote monitoring (RMON) provides advanced monitoring and reporting capabilities for statistics, history, alarms and events. RMON data is retrieved from the switch through a network management platform over SNMP.

### Quality of Service (QoS)

## Overview

- **Traffic prioritization**  
Provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to six hardware queues for more effective throughput
- **IEEE 802.1p/Q VLAN tagging**  
Delivers data to devices based on the priority and type of traffic; supports IEEE 802.1Q
- **Advanced classifier based QoS**  
Classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information.
- **Packet storm protection**  
Protects against unknown unicast, broadcast and multicast storms with user-defined thresholds
- **Rate limiting**  
Sets per-port ingress enforced maximums or percent minimum bandwidth per queue
- **Class of Service (CoS)**  
Sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number or source port
- **Powerful QoS feature**  
Supports the following congestion actions: strict priority queuing (SP) or weighted round robin (WRR) queuing. SP and WRR queuing can be configured on individual switch ports.

## Connectivity

- **IPv6 host**  
Enables switches to be managed and deployed at the IPv6 network's edge
- **IEEE 802.3X Flow Control**  
Provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node
- **IEEE 802.3af Power over Ethernet (PoE+)**  
Provides up to 30 W per port, which allows support of the latest PoE+ capable devices such as Video IP phones, wireless access points, and advanced pan/tilt/zoom security cameras, as well as any 15.4 W IEEE 802.3af-compliant end device; mitigates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments
- **PoE+ port availability**  
Ports 1–4 are PoE/PoE+ capable on the HPE OfficeConnect 1920S 8G PPOE+ 65W switch; ports 1–12 are PoE/PoE+ capable on the HPE OfficeConnect 1920S 24G 2SFP PPOE+ 185W switch; all ports provide PoE/PoE+ on the HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W switch; ports 1–24 are PoE/PoE+ capable on the HPE OfficeConnect 1920S 48G 4SFP PPOE+ 370W switch
- **Auto-PoE power configuration**  
The switch automatically assigns the required power to a port for a PD device based on Link Layer Discovery Protocol (LLDP). Optionally, the switch permits manual, per port, PoE power configuration
- **PoE shut down mode**  
A PoE scheduler provides the ability to define the hours of PoE power being supplied to a group of switch ports based on a 24-hour day. The scheduler enables the flexibility to select individual days of a week as well as reoccurrence on a weekly basis with a start and end date.
- **PoE power allocation**  
Support multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings
- **SFP ports for fiber connectivity**  
Provides fiber connections for uplinks and other connections across longer distances than copper cabling can support; SFP ports are in addition to available copper Ethernet ports, providing a higher total number of available ports. Two SFP ports available on 24 and four SFP ports on 48 port models
- **Loop protection**  
If the switch detects a loop, it disables the source port from forwarding data packets originating from the switch to avoid broadcast storms
- **Auto MDI/MDI-X**  
Adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports
- **Energy Efficient Ethernet (EEE)**

## Overview

Compliant with IEEE 802.3az standard requirements to save energy during periods of low data activity

- **Auto-port shut down**  
The switch saves power by automatically shutting down power to inactive ports. Power is restored on a port upon link detection
- **Energy savings status**  
The switch provides an estimated cumulative energy savings due to green Ethernet features being enabled
- **Energy-efficient cooling**  
Includes variable speed fans operating only at the speed necessary to maintain operating temperature to reduce excess noise and power consumption by the switch

## Security

- **Access Control Lists (ACLs)**  
Enables network traffic filtering by creating an ACL, add rules and match criteria to an ACL, and apply the ACL to permit or deny on one or more interfaces or a VLAN. Up to 50 inbound entries may be configured based on IPv4 source and destination IP and MAC address, Layer 4 ports and protocol type of the IPv4 packet.
- **RADIUS**  
The switch support RADIUS authentication and configuration of up to 8 RADIUS servers
- **RADIUS Accounting**  
A robust set of attributes and statistics are available for collecting information from the switch
- **IEEE 802.1X access control**  
Authentication of network users on a per port basis prior to permitting network access. Port VLAN includes RADIUS VLAN assignment, dynamic VLAN creation, guest VLAN or into an unauthenticated VLAN.
- **Switch 802.1X supplicant**  
Enables the switch to authenticate itself to a RADIUS server
- **Port isolation**  
Ports in a port isolation group are restricted from forwarding Layer 2 traffic between ports in that group; provides data privacy and security
- **Automatic denial-of-service protection**  
Monitors for malicious attacks and protects the network by blocking the attacks
- **Management password**  
Provides security so that only authorized access to the Web browser interface is allowed
- **Secure Sockets Layer (SSL)**  
Encrypts all HTTP traffic, secure access to the browser-based management of the switch

## Performance

- **Half-and full-duplex auto-negotiating capability on every port**  
doubles the throughput of every port
- **Selectable queue configurations**  
Allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- **IGMP snooping**  
Improves network performance through multicast filtering, instead of flooding traffic on all ports
- **SFP fiber uplinks**  
Provides greater distance connectivity using Gigabit Ethernet fiber uplinks

## Layer 2 switching

- **Spanning Tree Protocol (STP)**  
Supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **BPDU filtering**

## Overview

Drops BPDU packets when STP is enabled globally but disabled on a specific port

- **Jumbo frame support**  
Supports up to 9216 bytes frame size to improve the performance of large data transfers
- **VLAN support and tagging**  
Support for IEEE 802.1Q; 256 VLANs with a VLAN ID range of 2-4093

## Layer 3 services

- **Address Resolution Protocol (ARP)**  
Displays the MAC address of another IP host in the same subnet; supports static ARPs; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **DHCP relay**  
Simplifies management of DHCP addresses in networks with multiple subnets

## Layer 3 routing

- **Static IPv4 routing**  
Provides basic routing supporting up to 32 static routes to allow manual routing configuration
- **Link aggregation**  
Groups together multiple ports up to a maximum of eight ports per trunk either automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; help prevent traffic bottlenecks. The 8 port models support 4 trunks, 16 and 24 port models support 8 trunks, 48 port models support 16 trunks.

## Convergence

- **LLDP-MED (Media Endpoint Discovery)**  
Defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to configure network devices such as IP phones automatically
- **Auto voice VLAN**  
Recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones

## Warranty and support

- **Limited Lifetime Warranty**  
This series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period. See <http://www.hpe.com/networking/warrantysummary> for full warranty and support information included with your product purchase.

## Configuration

**Build To Order:** BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

|                                                                                                                                                                                   |                                        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| HPE OfficeConnect 1920S 8G Switch                                                                                                                                                 | JL380A                                 |
| <ul style="list-style-type: none"> <li>8 RJ-45 autosensing 10/100/1000 ports</li> <li>1U - Height (Desktop Model)</li> </ul>                                                      | See Configuration<br><b>NOTE: 2</b>    |
| PDU Cable NA/MX/TW/JP                                                                                                                                                             | JL380A#B2B                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                               |                                        |
| PDU Cable ROW                                                                                                                                                                     | JL380A#B2C                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                       |                                        |
| No Power Cord                                                                                                                                                                     | JL380A#AC3                             |
| <ul style="list-style-type: none"> <li>No Localized Power Cord Selected</li> </ul>                                                                                                |                                        |
| HPE OfficeConnect 1920S 8G PPOE+ 65W Switch                                                                                                                                       | JL383A                                 |
| <ul style="list-style-type: none"> <li>4 RJ-45 autosensing 10/100/1000 PoE+ ports</li> <li>4 RJ-45 autosensing 10/100/1000 ports</li> <li>1U - Height (Desktop Model)</li> </ul>  | See Configuration<br><b>NOTE: 2</b>    |
| PDU Cable NA/MX/TW/JP                                                                                                                                                             | JL383A#B2B                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                               |                                        |
| PDU Cable ROW                                                                                                                                                                     | JL383A#B2C                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                       |                                        |
| No Power Cord                                                                                                                                                                     | JL383A#AC3                             |
| <ul style="list-style-type: none"> <li>No Localized Power Cord Selected</li> </ul>                                                                                                |                                        |
| HPE OfficeConnect 1920S 24G 2SFP Switch                                                                                                                                           | JL381A                                 |
| <ul style="list-style-type: none"> <li>24 RJ-45 autosensing 10/100/1000 ports</li> <li>2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li> <li>1U - Height</li> </ul> | See Configuration<br><b>NOTE: 2, 3</b> |
| PDU Cable NA/MX/TW/JP                                                                                                                                                             | JL381A#B2B                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                               |                                        |
| PDU Cable ROW                                                                                                                                                                     | JL381A#B2C                             |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                       |                                        |
| No Power Cord                                                                                                                                                                     | JL381A#AC3                             |
| <ul style="list-style-type: none"> <li>No Localized Power Cord Selected</li> </ul>                                                                                                |                                        |
| HPE OfficeConnect 1920S 24G 2SFP PPOE+ 185W Switch                                                                                                                                | JL384A                                 |
| <ul style="list-style-type: none"> <li>12 RJ-45 autosensing 10/100/1000 PoE+ ports</li> </ul>                                                                                     | See Configuration                      |

## Configuration

|                                                                                                                                                                                                                                                                                                   |                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <ul style="list-style-type: none"> <li>• 12 RJ-45 autosensing 10/100/1000 ports</li> <li>• 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li> <li>• 1U - Height</li> </ul>                                                                                                           | <b>NOTE: 2, 3</b>                               |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                                                       | JL384A#B2B                                      |
| PDU Cable ROW <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                                                                                                                       | JL384A#B2C                                      |
| No Power Cord <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>                                                                                                                                                                                                | JL384A#AC3                                      |
| HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W Switch <ul style="list-style-type: none"> <li>• 24 RJ-45 autosensing 10/100/1000 PoE+ ports</li> <li>• 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li> <li>• 1U - Height</li> </ul>                                                    | JL385A<br>See Configuration<br><b>NOTE:2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                                                       | JL385A#B2B                                      |
| PDU Cable ROW <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                                                                                                                       | JL385A#B2C                                      |
| No Power Cord <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>                                                                                                                                                                                                | JL385A#AC3                                      |
| HPE OfficeConnect 1920S 48G 4SFP Switch <ul style="list-style-type: none"> <li>• 48 RJ-45 autosensing 10/100/1000 ports</li> <li>• 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers)</li> <li>• 1U - Height</li> </ul>                                                                   | JL382A<br>See Configuration<br><b>NOTE:2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                                                       | JL382A#B2B                                      |
| PDU Cable ROW <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                                                                                                                       | JL382A#B2C                                      |
| No Power Cord <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>                                                                                                                                                                                                | JL382A#AC3                                      |
| HPE OfficeConnect 1920S 48G 4SFP PPoE+ 370W Switch <ul style="list-style-type: none"> <li>• 24 RJ-45 autosensing 10/100/1000 PoE+ ports</li> <li>• 24 RJ-45 autosensing 10/100/1000 ports</li> <li>• 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers)</li> <li>• 1U - Height</li> </ul> | JL386A<br>See Configuration<br><b>NOTE:2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                                                       | JL386A#B2B                                      |

## Configuration

|                                                                                    |            |
|------------------------------------------------------------------------------------|------------|
| PDU Cable ROW                                                                      | JL386A#B2C |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW)</li> </ul>        |            |
| No Power Cord                                                                      | JL386A#AC3 |
| <ul style="list-style-type: none"> <li>No Localized Power Cord Selected</li> </ul> |            |

### Configuration Rules:

**Note 2** Localization (Wall Power Cord) required on orders without #B2B or #B2C (PDU Power Cord). (See Localization Menu)

**Note 3** The following Transceivers install into this switch:

|                                     |        |
|-------------------------------------|--------|
| HPE X121 1G SFP LC SX Transceiver   | J4858C |
| HPE X121 1G SFP LC LX Transceiver   | J4859C |
| HPE X121 1G SFP RJ45 T Transceiver  | J8177C |
| HPE X111 100M SFP LC FX Transceiver | J9054C |

**Remarks:** Drop down under power supply should offer the following options and results:  
 Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)  
 Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

## Rack Level Integration CTO Models

|                                                                                                                                                                                                                                        |                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| HPE OfficeConnect 1920S 24G 2SFP Switch                                                                                                                                                                                                | JL381A                                    |
| <ul style="list-style-type: none"> <li>24 RJ-45 autosensing 10/100/1000 ports</li> <li>2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li> <li>1U - Height</li> </ul>                                                      | See Configuration<br><b>NOTE: 1, 2, 3</b> |
| PDU Cable NA/MX/TW/JP                                                                                                                                                                                                                  | JL381A#B2B                                |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                    |                                           |
| PDU Cable ROW                                                                                                                                                                                                                          | JL381A#B2C                                |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW)</li> </ul>                                                                                                                                                            |                                           |
| No Power Cord                                                                                                                                                                                                                          | JL381A#AC3                                |
| <ul style="list-style-type: none"> <li>No Localized Power Cord Selected</li> </ul>                                                                                                                                                     |                                           |
| HPE OfficeConnect 1920S 24G 2SFP PPOE+ 185W Switch                                                                                                                                                                                     | JL384A                                    |
| <ul style="list-style-type: none"> <li>12 RJ-45 autosensing 10/100/1000 PoE+ ports</li> <li>12 RJ-45 autosensing 10/100/1000 ports</li> <li>2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li> <li>1U - Height</li> </ul> | See Configuration<br><b>NOTE: 1, 2, 3</b> |
| PDU Cable NA/MX/TW/JP                                                                                                                                                                                                                  | JL384A#B2B                                |
| <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>                                                                                                                                                    |                                           |



## Configuration

|                                                                                                                                                                                                                                                                                      |                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>                                                                                                                                                                                              | JL384A#B2C                                          |
| No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>                                                                                                                                                                                       | JL384A#AC3                                          |
| HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W Switch <ul style="list-style-type: none"><li>24 RJ-45 autosensing 10/100/1000 PoE+ ports</li><li>2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers)</li><li>1U - Height</li></ul>                                                 | JL385A<br>See Configuration<br><b>NOTE: 1, 2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li></ul>                                                                                                                                                                              | JL385A#B2B                                          |
| PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>                                                                                                                                                                                              | JL385A#B2C                                          |
| No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>                                                                                                                                                                                       | JL385A#AC3                                          |
| HPE OfficeConnect 1920S 48G 4SFP Switch <ul style="list-style-type: none"><li>48 RJ-45 autosensing 10/100/1000 ports</li><li>4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers)</li><li>1U - Height</li></ul>                                                                | JL382A<br>See Configuration<br><b>NOTE: 1, 2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li></ul>                                                                                                                                                                              | JL382A#B2B                                          |
| PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>                                                                                                                                                                                              | JL382A#B2C                                          |
| No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>                                                                                                                                                                                       | JL382A#AC3                                          |
| HPE OfficeConnect 1920S 48G 4SFP PPoE+ 370W Switch <ul style="list-style-type: none"><li>24 RJ-45 autosensing 10/100/1000 PoE+ ports</li><li>24 RJ-45 autosensing 10/100/1000 ports</li><li>4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers)</li><li>1U - Height</li></ul> | JL386A<br>See Configuration<br><b>NOTE: 1, 2, 3</b> |
| PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li></ul>                                                                                                                                                                              | JL386A#B2B                                          |
| PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>                                                                                                                                                                                              | JL386A#B2C                                          |
| No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>                                                                                                                                                                                       | JL386A#AC3                                          |

## Configuration

### Configuration Rules:

- Note 1**            The following Transceivers install into this switch:
- |                                     |        |
|-------------------------------------|--------|
| HPE X121 1G SFP LC SX Transceiver   | J4858C |
| HPE X121 1G SFP LC LX Transceiver   | J4859C |
| HPE X121 1G SFP RJ45 T Transceiver  | J8177C |
| HPE X111 100M SFP LC FX Transceiver | J9054C |
- Note 2**            Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) . (See Localization Menu)  
REMARK: When Switches/Routers are Factory Racked, Then #B2B, or #B2C should be the Defaulted Power Cable option on the Switches/Routers.  
#AC3 No Localized Power Cord Selected
- Remarks:**        If this switch is factory installed in any HPE Racks, Then the J9583A#0D1 is required.

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

## Transceivers

### SFP Transceivers

|                                     |        |
|-------------------------------------|--------|
| HPE X121 1G SFP LC SX Transceiver   | J4858C |
| HPE X121 1G SFP LC LX Transceiver   | J4859C |
| HPE X121 1G SFP RJ45 T Transceiver  | J8177C |
| HPE X120 1G SFP LC SX Transceiver   | JD118B |
| HPE X120 1G SFP LC LX Transceiver   | JD119B |
| HPE X120 1G SFP RJ45 T Transceiver  | JD089B |
| HPE X111 100M SFP LC FX Transceiver | J9054C |

## Cables

### Multi-Mode Cables

|                                                                    |        |
|--------------------------------------------------------------------|--------|
| HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable  | AJ833A |
| HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable  | AJ834A |
| HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable  | AJ835A |
| HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable  | AJ836A |
| HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable             | QK732A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable             | QK733A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable             | QK734A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable            | QK735A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable            | QK736A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable            | QK737A |

## Configuration

### Switch Enclosure Options

#### External/Redundant Power Supplies

HPE RPS1600 Redundant Power System

- Height = 1U
- includes 1 x c13, 1600w and Power Supply port

JG136A  
See Configuration  
**NOTE:2, 3, 4**

HPE RPS1600 1600W AC Power Supply

- Installs into JG136A only

JG137A  
See Configuration  
**NOTE:1, 3**

HPE RPS 800 Redundant Power Supply

- Installs into JH295A only

JD183A  
See Configuration  
**NOTE: 2, 5**

#### Configuration Rules:

- Note 1** If this power supply is selected, The JG136A - HP A-RPS1600 Redundant Power System must be on order or onsite.
- Note 2** Localization required.
- Note 3** Each switch will only support 1 JG136A and 1 JG137A Power supply systems.
- Note 4** This power supply only supported on switch JG926A and JG928A

#### External/Redundant Power Cables

HPE X290 1000 A JD5 2m RPS Cable

JD187A  
See Configuration  
**NOTE:1**

**Remarks:** These cables are used to connect the External Power System to Switch.

#### Configuration Rules:

- Note 1** This Cable is only supported on switch JG926A and JG928A when used with the RPS 1600 (JG136A)

#### External/Redundant Power Supplies

HPE X410 1U Universal 4-post Rackmount Kit

- Supported on JL381A, JL382A, JL384A, JL385A, JL386A

J9583A  
See Configuration  
**NOTE: 1**

#### Configuration Rules:

- Note 1** If this Mounting Kit is order with #OD1 then it integrates to the HP Network Rack. (not the switch)

## Configuration

## Technical Specifications

### HPE OfficeConnect 1920S 8G Switch (JL380A)

|                                   |                                                                                                                                                                                               |                                                                      |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| <b>I/O ports and slots</b>        | 8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                      |
| <b>Physical characteristics</b>   | <b>Dimensions</b>                                                                                                                                                                             | 10(w) x 6.28(d) x 1.73(h) in<br>(25.4 x 15.95 x 4.39 cm) (1U height) |
|                                   | <b>Weight</b>                                                                                                                                                                                 | 1.81 lb (0.82 kg)                                                    |
| <b>Memory and processor</b>       | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                     |                                                                      |
| <b>Performance</b>                | <b>100 Mb Latency</b>                                                                                                                                                                         | < 7.0 $\mu$ s                                                        |
|                                   | <b>1000 Mb Latency</b>                                                                                                                                                                        | < 2.4 $\mu$ s                                                        |
|                                   | <b>Throughput</b>                                                                                                                                                                             | up to 11.9 Mpps                                                      |
|                                   | <b>Routing/Switching capacity</b>                                                                                                                                                             | 16 Gbps                                                              |
|                                   | <b>Routing table size</b>                                                                                                                                                                     | 32 entries                                                           |
|                                   | <b>MAC address table size</b>                                                                                                                                                                 | 8,000 entries                                                        |
|                                   | <b>Reliability</b>                                                                                                                                                                            | <b>MTBF (years)</b>                                                  |
| <b>Environment</b>                | <b>Operating temperature</b>                                                                                                                                                                  | 32°F to 104°F (0°C to 40°C)                                          |
|                                   | <b>Operating relative humidity</b>                                                                                                                                                            | 15% to 95% @ 104°F (40°C)                                            |
|                                   | <b>Nonoperating/Storage temperature</b>                                                                                                                                                       | -40°F to 158°F (-40°C to 70°C)                                       |
|                                   | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                 | 15% to 95% @ 140°F (60°C)                                            |
|                                   | <b>Altitude</b>                                                                                                                                                                               | up to 10,000 ft (3 km)                                               |
|                                   | <b>Acoustic</b>                                                                                                                                                                               | Power: 0 dB no fan                                                   |
| <b>Electrical characteristics</b> | <b>Frequency</b>                                                                                                                                                                              | 50/60 Hz                                                             |
|                                   | <b>AC Voltage</b>                                                                                                                                                                             | 100 - 240 VAC                                                        |
|                                   | <b>Current</b>                                                                                                                                                                                | .2 A                                                                 |
|                                   | <b>Maximum power rating</b>                                                                                                                                                                   | 9.5 W                                                                |
|                                   | <b>Idle power</b>                                                                                                                                                                             | 8.2 W                                                                |
| <b>Safety</b>                     | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60825-1                                                                                                                    |                                                                      |
| <b>Emissions</b>                  | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                       |                                                                      |
| <b>Immunity</b>                   | <b>Generic</b>                                                                                                                                                                                | EN 55024, CISPR 24                                                   |
|                                   | <b>EN</b>                                                                                                                                                                                     | EN 55024, CISPR 24                                                   |
|                                   | <b>ESD</b>                                                                                                                                                                                    | IEC 61000-4-2                                                        |
|                                   | <b>Radiated</b>                                                                                                                                                                               | IEC 61000-4-3                                                        |
|                                   | <b>EFT/Burst</b>                                                                                                                                                                              | IEC 61000-4-4                                                        |
|                                   | <b>Surge</b>                                                                                                                                                                                  | IEC 61000-4-5                                                        |
|                                   | <b>Conducted</b>                                                                                                                                                                              | IEC 61000-4-6                                                        |
|                                   | <b>Power frequency magnetic field</b>                                                                                                                                                         | IEC 61000-4-8                                                        |
|                                   | <b>Voltage dips and</b>                                                                                                                                                                       | IEC 61000-4-11                                                       |

## Technical Specifications

|                          |                                                                                                                                                                                                                                                                                                                                                  |                             |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
|                          | <b>interruptions</b>                                                                                                                                                                                                                                                                                                                             |                             |
|                          | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2 |
|                          | <b>Flicker</b>                                                                                                                                                                                                                                                                                                                                   | EN 61000-3-3, IEC 61000-3-3 |
| <b>Device Management</b> | Web browser                                                                                                                                                                                                                                                                                                                                      |                             |
| <b>Services</b>          | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                             |

---

### HPE OfficeConnect 1920S 24G 2SFP Switch (JL381A)

|                                   |                                                                                                                                                                                                |                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>I/O ports and slots</b>        | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                          |
|                                   | 2 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)                                                                                                           |                                                                          |
| <b>Physical characteristics</b>   | <b>Dimensions</b>                                                                                                                                                                              | 17.42(w) x 9.69(d) x 1.73(h) in<br>(44.25 x 24.61 x 4.39 cm) (1U height) |
|                                   | <b>Weight</b>                                                                                                                                                                                  | 6 lb (2.72 kg)                                                           |
| <b>Memory and processor</b>       | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                      |                                                                          |
| <b>Performance</b>                | <b>100 Mb Latency</b>                                                                                                                                                                          | < 7.0 $\mu$ s                                                            |
|                                   | <b>1000 Mb Latency</b>                                                                                                                                                                         | < 2.0 $\mu$ s                                                            |
|                                   | <b>Throughput</b>                                                                                                                                                                              | up to 38.6 Mpps                                                          |
|                                   | <b>Routing/Switching capacity</b>                                                                                                                                                              | 52 Gbps                                                                  |
|                                   | <b>Routing table size</b>                                                                                                                                                                      | 32 entries                                                               |
|                                   | <b>MAC address table size</b>                                                                                                                                                                  | 8,000 entries                                                            |
| <b>Reliability</b>                | <b>MTBF (years)</b>                                                                                                                                                                            | 80                                                                       |
| <b>Environment</b>                | <b>Operating temperature</b>                                                                                                                                                                   | 32°F to 104°F (0°C to 40°C)                                              |
|                                   | <b>Operating relative humidity</b>                                                                                                                                                             | 15% to 95% @ 104°F (40°C)                                                |
|                                   | <b>Nonoperating/Storage temperature</b>                                                                                                                                                        | -40°F to 158°F (-40°C to 70°C)                                           |
|                                   | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                  | 15% to 95% @ 140°F (60°C)                                                |
|                                   | <b>Altitude</b>                                                                                                                                                                                | up to 10,000 ft (3 km)                                                   |
|                                   | <b>Acoustic</b>                                                                                                                                                                                | Power: 0 dB no fan                                                       |
| <b>Electrical characteristics</b> | <b>Frequency</b>                                                                                                                                                                               | 50/60 Hz                                                                 |
|                                   | <b>AC Voltage</b>                                                                                                                                                                              | 100 - 127 / 200 - 240 VAC                                                |
|                                   | <b>Current</b>                                                                                                                                                                                 | .5/.3 A                                                                  |
|                                   | <b>Maximum power rating</b>                                                                                                                                                                    | 15.7 W                                                                   |
|                                   | <b>Idle power</b>                                                                                                                                                                              | 11.6 W                                                                   |
| <b>Safety</b>                     | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1                                                                                                                    |                                                                          |
| <b>Emissions</b>                  | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                        |                                                                          |
| <b>Immunity</b>                   | <b>Generic</b>                                                                                                                                                                                 | EN 55024, CISPR 24                                                       |
|                                   | <b>EN</b>                                                                                                                                                                                      | EN 55024, CISPR 24                                                       |
|                                   | <b>ESD</b>                                                                                                                                                                                     | IEC 61000-4-2                                                            |
|                                   | <b>Radiated</b>                                                                                                                                                                                | IEC 61000-4-3                                                            |

## Technical Specifications

|                          |                                                                                                                                                                                                                                                                                                                                                  |                             |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
|                          | <b>EFT/Burst</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-4               |
|                          | <b>Surge</b>                                                                                                                                                                                                                                                                                                                                     | IEC 61000-4-5               |
|                          | <b>Conducted</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-6               |
|                          | <b>Power frequency magnetic field</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-8               |
|                          | <b>Voltage dips and interruptions</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-11              |
|                          | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2 |
|                          | <b>Flicker</b>                                                                                                                                                                                                                                                                                                                                   | EN 61000-3-3, IEC 61000-3-3 |
| <b>Device Management</b> | Web browser                                                                                                                                                                                                                                                                                                                                      |                             |
| <b>Notes</b>             | Use only supported genuine HPE mini-GBICs with your switch.                                                                                                                                                                                                                                                                                      |                             |
| <b>Services</b>          | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                             |

### HPE OfficeConnect 1920S 48G 4SFP Switch (JL382A)

|                                   |                                                                                                                                                                                                |                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                          |
|                                   | 4 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)                                                                                                           |                                                                          |
| <b>Physical characteristics</b>   | <b>Dimensions</b>                                                                                                                                                                              | 17.42(w) x 9.69(d) x 1.73(h) in<br>(44.25 x 24.61 x 4.39 cm) (1U height) |
|                                   | <b>Weight</b>                                                                                                                                                                                  | 7.3 lb (3.31 kg)                                                         |
| <b>Memory and processor</b>       | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                      |                                                                          |
| <b>Performance</b>                | <b>100 Mb Latency</b>                                                                                                                                                                          | < 7.0 $\mu$ s                                                            |
|                                   | <b>1000 Mb Latency</b>                                                                                                                                                                         | < 2.0 $\mu$ s                                                            |
|                                   | <b>Throughput</b>                                                                                                                                                                              | up to 77.3 Mpps                                                          |
|                                   | <b>Routing/Switching capacity</b>                                                                                                                                                              | 104 Gbps                                                                 |
|                                   | <b>Routing table size</b>                                                                                                                                                                      | 32 entries                                                               |
|                                   | <b>MAC address table size</b>                                                                                                                                                                  | 16,000 entries                                                           |
| <b>Reliability</b>                | <b>MTBF (years)</b>                                                                                                                                                                            | 61.73                                                                    |
| <b>Environment</b>                | <b>Operating temperature</b>                                                                                                                                                                   | 32°F to 104°F (0°C to 40°C)                                              |
|                                   | <b>Operating relative humidity</b>                                                                                                                                                             | 15% to 95% @ 104°F (40°C)                                                |
|                                   | <b>Nonoperating/Storage temperature</b>                                                                                                                                                        | -40°F to 158°F (-40°C to 70°C)                                           |
|                                   | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                  | 15% to 95% @ 140°F (60°C)                                                |
|                                   | <b>Altitude</b>                                                                                                                                                                                | up to 10,000 ft (3 km)                                                   |
|                                   | <b>Acoustic</b>                                                                                                                                                                                | Power: 0 dB no fan                                                       |
| <b>Electrical characteristics</b> | <b>Frequency</b>                                                                                                                                                                               | 50/60 Hz                                                                 |
|                                   | <b>AC Voltage</b>                                                                                                                                                                              | 100 - 127 / 200 - 240 VAC                                                |
|                                   | <b>Current</b>                                                                                                                                                                                 | .8/5 A                                                                   |
|                                   | <b>Maximum power rating</b>                                                                                                                                                                    | 32.2 W                                                                   |
|                                   | <b>Idle power</b>                                                                                                                                                                              | 23.3 W                                                                   |

## Technical Specifications

|                          |                                                                                                                                                                                                                                                                                                                                                  |                             |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>Safety</b>            | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1                                                                                                                                                                                                                                                                      |                             |
| <b>Emissions</b>         | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                                                                                                                                                                          |                             |
| <b>Immunity</b>          | <b>Generic</b>                                                                                                                                                                                                                                                                                                                                   | EN 55024, CISPR 24          |
|                          | <b>EN</b>                                                                                                                                                                                                                                                                                                                                        | EN 55024, CISPR 24          |
|                          | <b>ESD</b>                                                                                                                                                                                                                                                                                                                                       | IEC 61000-4-2               |
|                          | <b>Radiated</b>                                                                                                                                                                                                                                                                                                                                  | IEC 61000-4-3               |
|                          | <b>EFT/Burst</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-4               |
|                          | <b>Surge</b>                                                                                                                                                                                                                                                                                                                                     | IEC 61000-4-5               |
|                          | <b>Conducted</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-6               |
|                          | <b>Power frequency magnetic field</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-8               |
|                          | <b>Voltage dips and interruptions</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-11              |
|                          | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2 |
|                          | <b>Flicker</b>                                                                                                                                                                                                                                                                                                                                   | EN 61000-3-3, IEC 61000-3-3 |
| <b>Device Management</b> | Web browser                                                                                                                                                                                                                                                                                                                                      |                             |
| <b>Notes</b>             | Use only supported genuine HPE mini-GBICs with your switch.                                                                                                                                                                                                                                                                                      |                             |
| <b>Services</b>          | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                             |

### HPE OfficeConnect 1920S 8G PPoE+ 65W Switch (JL383A)

|                                 |                                                                                                                                                                                               |                                                                   |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| <b>I/O ports and slots</b>      | 4 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only                                                                                  |                                                                   |
|                                 | 4 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                   |
| <b>Physical characteristics</b> | <b>Dimensions</b>                                                                                                                                                                             | 10(w) x 6.28(d) x 1.73(h) in (25.4 x 15.95 x 4.39 cm) (1U height) |
|                                 | <b>Weight</b>                                                                                                                                                                                 | 2.01 lb (0.91 kg)                                                 |
| <b>Memory and processor</b>     | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                     |                                                                   |
| <b>Performance</b>              | <b>100 Mb Latency</b>                                                                                                                                                                         | < 7.0 $\mu$ s                                                     |
|                                 | <b>1000 Mb Latency</b>                                                                                                                                                                        | < 2.3 $\mu$ s                                                     |
|                                 | <b>Throughput</b>                                                                                                                                                                             | up to 11.9 Mpps                                                   |
|                                 | <b>Routing/Switching capacity</b>                                                                                                                                                             | 16 Gbps                                                           |
|                                 | <b>Routing table size</b>                                                                                                                                                                     | 32 entries                                                        |
|                                 | <b>MAC address table size</b>                                                                                                                                                                 | 8,000 entries                                                     |
| <b>Reliability</b>              | <b>MTBF (years)</b>                                                                                                                                                                           | 112.36                                                            |
| <b>Environment</b>              | <b>Operating temperature</b>                                                                                                                                                                  | 32°F to 104°F (0°C to 40°C)                                       |
|                                 | <b>Operating relative humidity</b>                                                                                                                                                            | 15% to 95% @ 104°F (40°C)                                         |
|                                 | <b>Nonoperating/Storage temperature</b>                                                                                                                                                       | -40°F to 158°F (-40°C to 70°C)                                    |
|                                 | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                 | 15% to 95% @ 140°F (60°C)                                         |



## Technical Specifications

|                                   |                                                                                                                                                                                                                                                                                                                                                  |                                                                             |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
|                                   | <b>Altitude</b>                                                                                                                                                                                                                                                                                                                                  | up to 10,000 ft (3 km)                                                      |
|                                   | <b>Acoustic</b>                                                                                                                                                                                                                                                                                                                                  | Power: 0 dB no fan                                                          |
| <b>Electrical characteristics</b> | <b>Frequency</b>                                                                                                                                                                                                                                                                                                                                 | 50/60 Hz                                                                    |
|                                   | <b>AC Voltage</b>                                                                                                                                                                                                                                                                                                                                | 100 - 240 VAC                                                               |
|                                   | <b>Current</b>                                                                                                                                                                                                                                                                                                                                   | .9 A                                                                        |
|                                   | <b>Maximum power rating</b>                                                                                                                                                                                                                                                                                                                      | 72.9 W                                                                      |
|                                   | <b>Idle power</b>                                                                                                                                                                                                                                                                                                                                | 9.7 W                                                                       |
|                                   | <b>PoE power</b>                                                                                                                                                                                                                                                                                                                                 | 65 W PoE+                                                                   |
|                                   | <b>Safety</b>                                                                                                                                                                                                                                                                                                                                    | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1 |
| <b>Emissions</b>                  | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                                                                                                                                                                          |                                                                             |
| <b>Immunity</b>                   | <b>Generic</b>                                                                                                                                                                                                                                                                                                                                   | EN 55024, CISPR 24                                                          |
|                                   | <b>EN</b>                                                                                                                                                                                                                                                                                                                                        | EN 55024, CISPR 24                                                          |
|                                   | <b>ESD</b>                                                                                                                                                                                                                                                                                                                                       | IEC 61000-4-2                                                               |
|                                   | <b>Radiated</b>                                                                                                                                                                                                                                                                                                                                  | IEC 61000-4-3                                                               |
|                                   | <b>EFT/Burst</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-4                                                               |
|                                   | <b>Surge</b>                                                                                                                                                                                                                                                                                                                                     | IEC 61000-4-5                                                               |
|                                   | <b>Conducted</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-6                                                               |
|                                   | <b>Power frequency magnetic field</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-8                                                               |
|                                   | <b>Voltage dips and interruptions</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-11                                                              |
|                                   | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2                                                 |
| <b>Flicker</b>                    | EN 61000-3-3, IEC 61000-3-3                                                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Device Management</b>          | Web browser                                                                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Services</b>                   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                                                                             |

### HPE OfficeConnect 1920S 24G 2SFP Ppoe+ 185W Switch (JL384A)

|                                 |                                                                                                                                                                                                |                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>I/O ports and slots</b>      | 12 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only                                                                                  |                                                                          |
|                                 | 12 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                          |
|                                 | 2 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)                                                                                                           |                                                                          |
| <b>Physical characteristics</b> | <b>Dimensions</b>                                                                                                                                                                              | 17.42(w) x 9.69(d) x 1.73(h) in<br>(44.25 x 24.61 x 4.39 cm) (1U height) |
|                                 | <b>Weight</b>                                                                                                                                                                                  | 7.3 lb (3.31 kg)                                                         |
| <b>Memory and processor</b>     | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                      |                                                                          |
| <b>Performance</b>              | <b>100 Mb Latency</b>                                                                                                                                                                          | < 7.0 $\mu$ s                                                            |
|                                 | <b>1000 Mb Latency</b>                                                                                                                                                                         | < 2.0 $\mu$ s                                                            |
|                                 | <b>Throughput</b>                                                                                                                                                                              | 38.6 Mpps                                                                |
|                                 | <b>Routing/Switching capacity</b>                                                                                                                                                              | 52 Gbps                                                                  |
|                                 | <b>Routing table size</b>                                                                                                                                                                      | 32 entries                                                               |

## Technical Specifications

|                             |                                                                                                                                                                                                                                                                                                                                                  |                                                                             |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
|                             | <b>MAC address table size</b>                                                                                                                                                                                                                                                                                                                    | 8,000 entries                                                               |
| <b>Reliability</b>          | <b>MTBF (years)</b>                                                                                                                                                                                                                                                                                                                              | 64.52                                                                       |
| <b>Environment</b>          | <b>Operating temperature</b>                                                                                                                                                                                                                                                                                                                     | 32°F to 104°F (0°C to 40°C)                                                 |
|                             | <b>Operating relative humidity</b>                                                                                                                                                                                                                                                                                                               | 15% to 95% @ 104°F (40°C)                                                   |
|                             | <b>Nonoperating/Storage temperature</b>                                                                                                                                                                                                                                                                                                          | -40°F to 158°F (-40°C to 70°C)                                              |
|                             | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                                                                                                                                                                    | 15% to 95% @ 140°F (60°C)                                                   |
|                             | <b>Altitude</b>                                                                                                                                                                                                                                                                                                                                  | up to 10,000 ft (3 km)                                                      |
|                             | <b>Acoustic</b>                                                                                                                                                                                                                                                                                                                                  | Power: 36 dB                                                                |
|                             | <b>Electrical characteristics</b>                                                                                                                                                                                                                                                                                                                | <b>Frequency</b>                                                            |
| <b>AC Voltage</b>           |                                                                                                                                                                                                                                                                                                                                                  | 100 - 127 / 200 - 240 VAC                                                   |
| <b>Current</b>              |                                                                                                                                                                                                                                                                                                                                                  | 2.6/1.3 A                                                                   |
| <b>Maximum power rating</b> |                                                                                                                                                                                                                                                                                                                                                  | 207.9 W                                                                     |
| <b>Idle power</b>           |                                                                                                                                                                                                                                                                                                                                                  | 19 W                                                                        |
| <b>PoE power</b>            |                                                                                                                                                                                                                                                                                                                                                  | 185 W PoE+                                                                  |
| <b>Safety</b>               |                                                                                                                                                                                                                                                                                                                                                  | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1 |
| <b>Emissions</b>            | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                                                                                                                                                                          |                                                                             |
| <b>Immunity</b>             | <b>Generic</b>                                                                                                                                                                                                                                                                                                                                   | EN 55024, CISPR 24                                                          |
|                             | <b>EN</b>                                                                                                                                                                                                                                                                                                                                        | EN 55024, CISPR 24                                                          |
|                             | <b>ESD</b>                                                                                                                                                                                                                                                                                                                                       | IEC 61000-4-2                                                               |
|                             | <b>Radiated</b>                                                                                                                                                                                                                                                                                                                                  | IEC 61000-4-3                                                               |
|                             | <b>EFT/Burst</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-4                                                               |
|                             | <b>Surge</b>                                                                                                                                                                                                                                                                                                                                     | IEC 61000-4-5                                                               |
|                             | <b>Conducted</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-6                                                               |
|                             | <b>Power frequency magnetic field</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-8                                                               |
|                             | <b>Voltage dips and interruptions</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-11                                                              |
|                             | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2                                                 |
| <b>Flicker</b>              | EN 61000-3-3, IEC 61000-3-3                                                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Device Management</b>    | Web browser                                                                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Notes</b>                | Use only supported genuine HPE mini-GBICs with your switch.                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Services</b>             | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                                                                             |

### HPE OfficeConnect 1920S 24G 2SFP PoE+ 370W Switch (JL385A)

|                                 |                                                                                                               |                                                                          |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>I/O ports and slots</b>      | 24 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                          |
|                                 | 2 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)                          |                                                                          |
| <b>Physical characteristics</b> | <b>Dimensions</b>                                                                                             | 17.42(w) x 12.7(d) x 1.73(h) in<br>(44.25 x 32.26 x 4.39 cm) (1U height) |
|                                 | <b>Weight</b>                                                                                                 | 9.7 lb (4.4 kg)                                                          |

## Technical Specifications

|                             |                                                                                                                                                                                                                                                                                                                                                  |                                                                             |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>Memory and processor</b> | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                                                                                                                                                                        |                                                                             |
| <b>Performance</b>          | <b>100 Mb Latency</b>                                                                                                                                                                                                                                                                                                                            | < 7.0 $\mu$ s                                                               |
|                             | <b>1000 Mb Latency</b>                                                                                                                                                                                                                                                                                                                           | < 2.0 $\mu$ s                                                               |
|                             | <b>Throughput</b>                                                                                                                                                                                                                                                                                                                                | 77.3 Mpps                                                                   |
|                             | <b>Routing/Switching capacity</b>                                                                                                                                                                                                                                                                                                                | 52 Gbps                                                                     |
|                             | <b>Routing table size</b>                                                                                                                                                                                                                                                                                                                        | 32 entries                                                                  |
|                             | <b>MAC address table size</b>                                                                                                                                                                                                                                                                                                                    | 16,000 entries                                                              |
|                             | <b>Reliability</b>                                                                                                                                                                                                                                                                                                                               | <b>MTBF (years)</b>                                                         |
| <b>Environment</b>          | <b>Operating temperature</b>                                                                                                                                                                                                                                                                                                                     | 32°F to 104°F (0°C to 40°C)                                                 |
|                             | <b>Operating relative humidity</b>                                                                                                                                                                                                                                                                                                               | 15% to 95% @ 104°F (40°C)                                                   |
|                             | <b>Nonoperating/Storage temperature</b>                                                                                                                                                                                                                                                                                                          | -40°F to 158°F (-40°C to 70°C)                                              |
|                             | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                                                                                                                                                                    | 15% to 95% @ 140°F (60°C)                                                   |
|                             | <b>Altitude</b>                                                                                                                                                                                                                                                                                                                                  | up to 10,000 ft (3 km)                                                      |
|                             | <b>Acoustic</b>                                                                                                                                                                                                                                                                                                                                  | Power: 45 dB                                                                |
|                             | <b>Electrical characteristics</b>                                                                                                                                                                                                                                                                                                                | <b>Frequency</b>                                                            |
| <b>AC Voltage</b>           |                                                                                                                                                                                                                                                                                                                                                  | 100 - 127 / 200 - 240 VAC                                                   |
| <b>Current</b>              |                                                                                                                                                                                                                                                                                                                                                  | 3.5/1.9 A                                                                   |
| <b>Maximum power rating</b> |                                                                                                                                                                                                                                                                                                                                                  | 435 W                                                                       |
| <b>Idle power</b>           |                                                                                                                                                                                                                                                                                                                                                  | 34.2 W                                                                      |
| <b>PoE power</b>            |                                                                                                                                                                                                                                                                                                                                                  | 370 W PoE+                                                                  |
| <b>Safety</b>               |                                                                                                                                                                                                                                                                                                                                                  | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1 |
| <b>Emissions</b>            | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                                                                                                                                                                          |                                                                             |
| <b>Immunity</b>             | <b>Generic</b>                                                                                                                                                                                                                                                                                                                                   | EN 55024, CISPR 24                                                          |
|                             | <b>EN</b>                                                                                                                                                                                                                                                                                                                                        | EN 55024, CISPR 24                                                          |
|                             | <b>ESD</b>                                                                                                                                                                                                                                                                                                                                       | IEC 61000-4-2                                                               |
|                             | <b>Radiated</b>                                                                                                                                                                                                                                                                                                                                  | IEC 61000-4-3                                                               |
|                             | <b>EFT/Burst</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-4                                                               |
|                             | <b>Surge</b>                                                                                                                                                                                                                                                                                                                                     | IEC 61000-4-5                                                               |
|                             | <b>Conducted</b>                                                                                                                                                                                                                                                                                                                                 | IEC 61000-4-6                                                               |
|                             | <b>Power frequency magnetic field</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-8                                                               |
|                             | <b>Voltage dips and interruptions</b>                                                                                                                                                                                                                                                                                                            | IEC 61000-4-11                                                              |
|                             | <b>Harmonics</b>                                                                                                                                                                                                                                                                                                                                 | EN 61000-3-2, IEC 61000-3-2                                                 |
|                             | <b>Flicker</b>                                                                                                                                                                                                                                                                                                                                   | EN 61000-3-3, IEC 61000-3-3                                                 |
| <b>Device Management</b>    | Web browser                                                                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Notes</b>                | Use only supported genuine HPE mini-GBICs with your switch.                                                                                                                                                                                                                                                                                      |                                                                             |
| <b>Services</b>             | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                                                                             |

## Technical Specifications

### HPE OfficeConnect 1920S 48G 4SFP PPoE+ 370W Switch (JL386A)

|                                   |                                                                                                                                                                                                |                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>I/O ports and slots</b>        | 24 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only                                                                                  |                                                                          |
|                                   | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |                                                                          |
|                                   | 4 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)                                                                                                           |                                                                          |
| <b>Physical characteristics</b>   | <b>Dimensions</b>                                                                                                                                                                              | 17.42(w) x 12.7(d) x 1.73(h) in<br>(44.25 x 32.26 x 4.39 cm) (1U height) |
|                                   | <b>Weight</b>                                                                                                                                                                                  | 9.7 lb (4.4 kg)                                                          |
| <b>Memory and processor</b>       | ARM Cortex-A9 @ 400 MHz, 256 MB SDRAM, 64 MB flash; packet buffer: 1.5 MB                                                                                                                      |                                                                          |
| <b>Performance</b>                | <b>100 Mb Latency</b>                                                                                                                                                                          | < 7.0 $\mu$ s                                                            |
|                                   | <b>1000 Mb Latency</b>                                                                                                                                                                         | < 2.0 $\mu$ s                                                            |
|                                   | <b>Throughput</b>                                                                                                                                                                              | 77.3 Mpps                                                                |
|                                   | <b>Routing/Switching capacity</b>                                                                                                                                                              | 104 Gbps                                                                 |
|                                   | <b>Routing table size</b>                                                                                                                                                                      | 32 entries                                                               |
|                                   | <b>MAC address table size</b>                                                                                                                                                                  | 16,000 entries                                                           |
| <b>Reliability</b>                | <b>MTBF (years)</b>                                                                                                                                                                            | 45                                                                       |
| <b>Environment</b>                | <b>Operating temperature</b>                                                                                                                                                                   | 32°F to 104°F (0°C to 40°C)                                              |
|                                   | <b>Operating relative humidity</b>                                                                                                                                                             | 15% to 95% @ 104°F (40°C)                                                |
|                                   | <b>Nonoperating/Storage temperature</b>                                                                                                                                                        | -40°F to 158°F (-40°C to 70°C)                                           |
|                                   | <b>Nonoperating/Storage relative humidity</b>                                                                                                                                                  | 15% to 95% @ 140°F (60°C)                                                |
|                                   | <b>Altitude</b>                                                                                                                                                                                | up to 10,000 ft (3 km)                                                   |
|                                   | <b>Acoustic</b>                                                                                                                                                                                | Power: 45 dB                                                             |
| <b>Electrical characteristics</b> | <b>Frequency</b>                                                                                                                                                                               | 50/60 Hz                                                                 |
|                                   | <b>AC Voltage</b>                                                                                                                                                                              | 100 - 127 / 200 - 240 VAC                                                |
|                                   | <b>Current</b>                                                                                                                                                                                 | 5.1/2.6 A                                                                |
|                                   | <b>Maximum power rating</b>                                                                                                                                                                    | 481 W                                                                    |
|                                   | <b>Idle power</b>                                                                                                                                                                              | 54.8 W                                                                   |
|                                   | <b>PoE power</b>                                                                                                                                                                               | 370 W PoE+                                                               |
| <b>Safety</b>                     | UL 60950-1; IEC 60950-1; EN 60950-1; CAN/ CSA-C22.2 No. 60950-1; EN 60825-1                                                                                                                    |                                                                          |
| <b>Emissions</b>                  | VCCI Class A; CNS 13438; ICES-003 Issue 5 Class A; FCC CFR 47 Part 15, Class A; EN 55032: 2015/CISPR-32                                                                                        |                                                                          |
| <b>Immunity</b>                   | <b>Generic</b>                                                                                                                                                                                 | EN 55024, CISPR 24                                                       |
|                                   | <b>EN</b>                                                                                                                                                                                      | EN 55024, CISPR 24                                                       |
|                                   | <b>ESD</b>                                                                                                                                                                                     | IEC 61000-4-2                                                            |
|                                   | <b>Radiated</b>                                                                                                                                                                                | IEC 61000-4-3                                                            |
|                                   | <b>EFT/Burst</b>                                                                                                                                                                               | IEC 61000-4-4                                                            |
|                                   | <b>Surge</b>                                                                                                                                                                                   | IEC 61000-4-5                                                            |
|                                   | <b>Conducted</b>                                                                                                                                                                               | IEC 61000-4-6                                                            |
|                                   | <b>Power frequency</b>                                                                                                                                                                         | IEC 61000-4-8                                                            |

## Technical Specifications

### magnetic field

**Voltage dips and interruptions** IEC 61000-4-11

**Harmonics** EN 61000-3-2, IEC 61000-3-2

**Flicker** EN 61000-3-3, IEC 61000-3-3

### Device Management

Web browser

### Notes

Use only supported genuine HPE mini-GBICs with your switch.

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### Standards and protocols Denial of service protection

(applies to all products in series) CPU DoS Protection

#### General Protocols

IEEE 802.1D MAC Bridges

IEEE 802.1p Priority

IEEE 802.1Q VLANs

IEEE 802.1s (MSTP)

IEEE 802.1w Rapid Reconfiguration of Spanning Tree

IEEE 802.3ad Link Aggregation Control Protocol (LACP)

IEEE 802.3x Flow Control

IEEE 802.3 Type 10BASE-T

IEEE 802.3i 10BASE-T

IEEE 802.3ab 1000BASE-T

IEEE 802.3z 1000BASE-X

### RADIUS Server

#### RADIUS server configuration options

IP/Address or Hostname

Friendly server name

Port Number (1-65335) Default = 1812

Secret key

Message Authenticator – enable or disable

#### RADIUS server summarized statistics

Client IP address / hostname

Round trip time

Access requests

Access rejects

Pending requests

Timeouts

Packets Dropped

### RADIUS Accounting

#### RADIUS accounting server configurations options

IP Address or Hostname

Friendly server name

Port number – (1-65335) Default = 1813

Secret Key

#### RADIUS accounting attributes

RADIUS\_ATTR\_TYPE\_USER\_NAME

RADIUS\_ATTR\_TYPE\_USER\_PASSWORD

RADIUS\_ATTR\_TYPE\_NAS\_IP\_ADDRESS

## Technical Specifications

RADIUS\_ATTR\_TYPE\_NAS\_PORT  
 RADIUS\_ATTR\_TYPE\_SERVICE\_TYPE  
 RADIUS\_ATTR\_TYPE\_FRAMED\_IP\_ADDRESS  
 RADIUS\_ATTR\_TYPE\_FILTER\_ID  
 RADIUS\_ATTR\_TYPE\_FRAMED\_MTU  
 RADIUS\_ATTR\_TYPE\_REPLY\_MESSAGE  
 RADIUS\_ATTR\_TYPE\_STATE  
 RADIUS\_ATTR\_TYPE\_CLASS  
 RADIUS\_ATTR\_TYPE\_SESSION\_TIMEOUT  
 RADIUS\_ATTR\_TYPE\_TERMINATION\_ACTION  
 RADIUS\_ATTR\_TYPE\_CALLED\_STATION\_ID  
 RADIUS\_ATTR\_TYPE\_CALLING\_STATION\_ID  
 RADIUS\_ATTR\_TYPE\_NAS\_IDENTIFIER  
 RADIUS\_ATTR\_TYPE\_ACCT\_STATUS\_TYPE  
 RADIUS\_ATTR\_TYPE\_ACCT\_INPUT\_OCTETS  
 RADIUS\_ATTR\_TYPE\_ACCT\_OUTPUT\_OCTETS  
 RADIUS\_ATTR\_TYPE\_ACCT\_SESSION\_ID  
 RADIUS\_ATTR\_TYPE\_ACCT\_SESSION\_TIME  
 RADIUS\_ATTR\_TYPE\_ACCT\_TERMINATE\_CAUSE  
 RADIUS\_ATTR\_TYPE\_ACCT\_G\_IBYTES  
 RADIUS\_ATTR\_TYPE\_ACCT\_G\_OBYTES  
 RADIUS\_ATTR\_TYPE\_NAS\_PORT\_TYPE  
 RADIUS\_ATTR\_TYPE\_TUNNEL\_TYPE  
 RADIUS\_ATTR\_TYPE\_TUNNEL\_MEDIUM\_TYPE  
 RADIUS\_ATTR\_TYPE\_EAP\_MESSAGE  
 RADIUS\_ATTR\_TYPE\_MESSAGE\_AUTHENTICATOR  
 RADIUS\_ATTR\_TYPE\_TUNNEL\_PRIVATE\_GROUP\_ID

### RADIUS accounting summarized statistics

Accounting Requests  
 Pending Requests  
 Timeouts  
 Packets Dropped

### MIB support

RFC 2819 RMON-MIB  
 HC-ALARM-MIB  
 SNMP-FRAMEWORK-MIB  
 SNMP-NOTIFICATION-MIB  
 SNMP-USER-BASED-SM-MIB  
 SR-AGENT-INFO-MIB  
 BRIDGE-MIB (IEEE 802.1Q)  
 Q-BRIDGE-MIB (RFC 2674)  
 LLDP-MIB (IEEE 802.3AB)  
 LLDP-EXT-MED-MIB  
 LAG-MIB (IEEE 802.3ad)  
 RADIUS-ACC-CLIENT-MIB  
 EtherLike-MIB  
 IF-MIB (RFC 2863)  
 RFC1213-MIB  
 Power Ethernet MIB (RFC3621)

### HPE Private MIBS

| MIB Description  | OID                         | Node Module | Object Name          |
|------------------|-----------------------------|-------------|----------------------|
| Software Version | 1.3.6.1.4.1.11.2.36.1.1.2.6 | SEMI-MIB    | hpHttpMgVersion      |
| ROM Version      | 1.3.6.1.4.1.11.2.36.1.1.2.8 | SEMI-MIB    | hpHttpMgROMVersion   |
| Serial Number    | 1.3.6.1.4.1.11.2.36.1.1.2.9 | SEMI-MIB    | hpHttpMgSerialNumber |

---

**Technical Specifications**

---

**sysOID – identifier MIB  
objects**

|                                          |                             |
|------------------------------------------|-----------------------------|
| JL380A HPE 1920S 8G Switch               | 1.3.6.1.4.1.11.2.3.7.11.183 |
| JL381A HPE 1920S 24G Switch              | 1.3.6.1.4.1.11.2.3.7.11.184 |
| JL382A HPE 1920S 48G Switch              | 1.3.6.1.4.1.11.2.3.7.11.185 |
| JL383A HPE 1920S 8G PPOE+ (65W) Switch   | 1.3.6.1.4.1.11.2.3.7.11.186 |
| JL384A HPE 1920S 24G PPOE+ (185W) Switch | 1.3.6.1.4.1.11.2.3.7.11.187 |
| JL385A HPE 1920S 24G PPOE+ (370W) Switch | 1.3.6.1.4.1.11.2.3.7.11.188 |
| JL386A HPE 1920S 48G PPOE+ (370W) Switch | 1.3.6.1.4.1.11.2.3.7.11.198 |

---

---

**Accessories****HPE OfficeConnect 1920S Switch Series accessories****Transceivers**

|                                     |        |
|-------------------------------------|--------|
| HPE X121 1G SFP LC SX Transceiver   | J4858C |
| HPE X121 1G SFP LC LX Transceiver   | J4859C |
| HPE X121 1G SFP RJ45 T Transceiver  | J8177C |
| HPE X111 100M SFP LC FX Transceiver | J9054C |

**Cables**

|                                                                    |        |
|--------------------------------------------------------------------|--------|
| HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable  | AJ833A |
| HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable  | AJ834A |
| HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable  | AJ835A |
| HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable  | AJ836A |
| HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable             | QK732A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable             | QK733A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable             | QK734A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable            | QK735A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable            | QK736A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable            | QK737A |

**Mounting Kit**

|                                            |        |
|--------------------------------------------|--------|
| HPE X410 1U Universal 4-post Rackmount Kit | J9583A |
|--------------------------------------------|--------|

---



## Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

|                                                                                                                                                                                                         |                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>HPE X121 1G SFP LC SX Transceiver</b> (J4858C)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.</p> | <p><b>Ports</b></p> <p><b>Physical characteristics</b></p> <p><b>Environment</b></p> <p><b>Electrical characteristics</b></p> <p><b>Cabling</b></p> | <p>1 LC 1000BASE-SX port; Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)<br/>Weight: 0.04 lb. (0.02 kg)<br/>Transceiver form factor: SFP</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)<br/>Operating relative humidity: 5% to 85%, noncondensing<br/>Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)<br/>Altitude: up to 10,000 ft. (3 km)</p> <p>Power consumption typical: 0.4 W<br/>Power consumption maximum: 0.7 W</p> <p>Type:</p> <ul style="list-style-type: none"> <li>62.5/125 <math>\mu\text{m}</math> or 50/125 <math>\mu\text{m}</math> (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;</li> </ul> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>2-220 m (62.5 <math>\mu\text{m}</math> core diameter, 160 MHz*km bandwidth)</li> <li>2-275 m (62.5 <math>\mu\text{m}</math> core diameter, 200 MHz*km bandwidth)</li> <li>2-500 m (50 <math>\mu\text{m}</math> core diameter, 400 MHz*km bandwidth)</li> <li>2-550 m (50 <math>\mu\text{m}</math> core diameter, 500 MHz*km bandwidth)</li> </ul> <p>Cable length: 2-550m<br/>Fiber type: Multi Mode</p> |
| <p><b>HPE X121 1G SFP LC LX Transceiver</b> (J4859C)</p> <p>HPE X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.</p>                            | <p><b>Ports</b></p> <p><b>Physical characteristics</b></p> <p><b>Environment</b></p> <p><b>Cabling</b></p> <p><b>Services</b></p>                   | <p>1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm)<br/>Weight: 0.04 lb. (0.02 kg)</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)<br/>Operating relative humidity: 0% to 85%, noncondensing<br/>Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C)<br/>Altitude: up to 10,000 ft. (3 km)</p> <p>Type:</p> <ul style="list-style-type: none"> <li>Either single mode or multimode; 62.5/125 <math>\mu\text{m}</math> or 50/125 <math>\mu\text{m}</math> (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2</li> </ul> <p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.</p>                                                                     |

## Accessory Product Details

Type B1;

Maximum distance:

- 2-550 m (multimode 62.5  $\mu$ m core diameter, 500 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu$ m core diameter, 400 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu$ m core diameter, 500 MHz\*km bandwidth)
- 2-10,000 m (single-mode fiber)

### Notes

A mode conditioning patch cord may be needed in some multimode fiber installations.

Wavelength: 1310nm

Power Consumption: < 500mW Typical

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HPE X121 1G SFP RJ45 T Transceiver (J8177C)

#### Ports

1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T); Duplex: full only

#### Physical characteristics

Dimensions: 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)

Weight: 0.06 lb. (0.03 kg)

HPE X121 1G SFP RJ45 T Transceiver: An SFP format gigabit transceiver with RJ45 connectors using 1000BaseT technology.

#### Environment

Operating temperature: 32°F to 158°F (0°C to 70°C); with 100 LFM airflow over the SFP module

Operating relative humidity: 0% to 95% @ 75°F (25°C), noncondensing

Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)

Nonoperating/Storage relative humidity: 0% to 95% @ 77°F (25°C), noncondensing

Altitude: up to 10,000 ft. (3000 km)

#### Cabling

Cable type:

1000BASE-T: Category 5 (5E or better recommended), 100  $\Omega$  differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;

Maximum distance:

- 100 m

#### Notes

Power consumption is nominally 1 watt.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J8177C 1000Base-T Mini-GBIC" on the "HPE Mini-GBICs and SFPs" Manuals Web page.

The J8177C Gigabit copper mini-GBIC is not supported on dual-personality ports.

The J8177C is capable of 100 Mb operation. This is supported on only the HPE E8200zl, E5400zl, and HPE E6200-24G-mGBIC yl Switches using

## Accessory Product Details

software version K.12.21 or later. Use the "auto-100" port setting to enable 100 Mb operation.

Important: The earlier J8177B does not support 100 Mb operation. When used in the Switch gl 20-Port 10/100/1000 Module (J4908A), the J8177C mini-GBIC can be installed in either the upper or lower mini-GBIC port, but will block access to the other port.

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable (AJ833A)**

### Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50  $\pm$  3.0 $\mu\text{m}$  Cladding diameter: 125  $\pm$  2.0 $\mu\text{m}$  Coating diameter: 245  $\pm$  10 $\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable**

### Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for

## Accessory Product Details

(AJ834A)

distances of up to 300 m

### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu$ m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu$ m multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable**  
(AJ835A)

### Cabling

#### Cable type:

50/125  $\mu$ m (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu$ m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu$ m

## Accessory Product Details

multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.

- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable (AJ836A)**

### Cabling

#### Cable type:

50/125  $\mu$ m core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125  $\mu$ m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50  $\pm$  3.0 $\mu$ m Cladding diameter: 125  $\pm$  2.0 $\mu$ m Coating diameter: 245  $\pm$  10 $\mu$ m
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu$ m multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level

## Accessory Product Details

descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable (AJ837A)**

### Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable (AJ838A)**

### Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm$

## Accessory Product Details

- 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable (AJ839A)

### Cabling

#### Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @

## Accessory Product Details

- 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HPE Premier Flex LC/LC Notes Multi-mode OM4 2 fiber 1m Cable (QK732A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HPE Premier Flex LC/LC Notes Multi-mode OM4 2 fiber 2m Cable (QK733A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise



## Accessory Product Details

sales office.

---

**HPE Premier Flex LC/LC Notes**  
**Multi-mode OM4 2 fiber**  
**5m Cable (QK734A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

**HPE Premier Flex LC/LC Notes**  
**Multi-mode OM4 2 fiber**  
**15m Cable (QK735A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

**HPE Premier Flex LC/LC Notes**  
**Multi-mode OM4 2 fiber**  
**30m Cable (QK736A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating

## Accessory Product Details

diameter: 245 ± 10um

- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths > 30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HPE Premier Flex LC/LC Notes Multi-mode OM4 2 fiber 50m Cable (QK737A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths > 30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

## Summary of Changes

| Date        | Version History     | Action  | Description of Change:                 |
|-------------|---------------------|---------|----------------------------------------|
| 16-May-2017 | From Version 1 to 2 | Changed | Edits made on Technical Specifications |
| 06-Mar-2017 | Version 1           | Created | Document creation                      |



**Sign up for updates**

© Copyright 2017 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00001630 - 15846 - Worldwide - V2 - 16-May-2017

